

	STM 1612 1270 dpi D3 (Landscape)	STM 1612 2400 dpi D3 (Landscape)	STM 1621 P3 (Portrait)	STM 2316 D5 (Landscape)	STM 3124 D6 (Landscape)	STM 4126 D7 (Landscape)
Rahmengröße in mm Frame size in inch	1850 x 1450 73" x 57"	1850 x 1450 73" x 57"	2300 x 2700 90.5" x 106"	2700 x 1800 106" x 71"	3400 x 2600 134" x 102"	4600 x 2800 181" x 110"
Bebildungsgröße in mm Image size in inch	1600 x 1200 63" x 47.25"	1600 x 1200 63" x 47.25"	1600 x 2100 63" x 83"	2300 x 1600 90.5" x 63"	3100 x 2400 122" x 94.5"	4100 x 2600 161" x 102.25"
Breite / Width in mm / inch Höhe / Height in mm / inch Tiefe / Depth in mm / inch	3120 / 123" 2225 / 87.5" 1893 / 74.5"	3120 / 123" 2225 / 87.5" 1893 / 74.5"	2600 / 102" 3500 / 138" 2100 / 83"	3800 / 150" 2740 / 108" 2090 / 82"	4600 / 181" 3540 / 140" 2090 / 82"	5600 / 221" 3740 / 148" 2090 / 82"
Gewicht / Weight Netto in kg / lb Gewicht / Weight Brutto in kg / lb	1995 / 4389 2336 / 5150	1995 / 4389 2336 / 5150	2550 / 5610 3990 / 8778	2650 / 5842 4142 / 9133	2999 / 6612 4492 / 9903	3850 / 8488 5343 / 11779

Wichtig! Für den Service der Maschinen wird beidseitig ein Freiraum von 400 mm (in der Beite) benötigt. Für eine optimale Platzierung der Maschine muss folglich 800 mm zusätzlicher Raum eingeplant werden.
Für die STM 1612 wird ca. 300 mm an beiden Seiten benötigt.

It is important to have an additional 400 mm / 16" space on the left and right side (width) of the machine, a total of 800 mm / 32" to be able to open the cover for maintenance!
For STM 1612 we need to allow app. 300 mm / 12" on both sides. A total of 600 mm / 24".

Waver

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

