

Technical Data	SEFAR® LDS 1330	SEFAR® LDS 4060
Solid diode laser (Class 1 laser)	<ul style="list-style-type: none"> Wavelength approx. 405 nm Laser power approx. 180 mW Laser point Ø 20 µm 7000 hrs guaranteed lifetime 	<ul style="list-style-type: none"> Wave length approx. 405 nm Laser power approx. 180 mW Laser point Ø 30 µm 7000 hrs guaranteed lifetime
Resolution	<ul style="list-style-type: none"> 1200 dpi and 2400 dpi settings 	<ul style="list-style-type: none"> 850 dpi and 1700 dpi settings
Exposure size	<ul style="list-style-type: none"> Approx. 13 x 30 cm (5.1 x 11.8 in) 	<ul style="list-style-type: none"> Imaging width approx. 40 cm (15.7 in), length adjustable
Frame format	<ul style="list-style-type: none"> Frame format approx. 40 x 45 cm (15.7 x 17.7 in) Up to 6 cm (2.36 in) screen frame height 	<ul style="list-style-type: none"> Frame width approx. 60 cm (23.6 in), length adjustable All common screen frame heights
Stencil imaging – Output	<ul style="list-style-type: none"> Data loading Automatic frame loading Imaging Automatic frame unloading <p style="text-align: right;"><i>ca. 35 Stk/Std. fully automated</i></p>	<ul style="list-style-type: none"> Data loading Frame loading Imaging Frame unloading
Interface/network	<ul style="list-style-type: none"> LAN data link: RJ45 10/100 BaseT 	<ul style="list-style-type: none"> LAN data link: RJ45 10/100 BaseT
Maintenance	<ul style="list-style-type: none"> Easy exchange of the laser bridge Modem for remote maintenance 	<ul style="list-style-type: none"> Easy exchange of the laser bridge Modem for remote maintenance
Dimensions/power supply	<ul style="list-style-type: none"> Weight approx. 400 kg (880 lbs) Dimensions approx.: 100 x 165 x 105 cm (39.4 x 64.9 x 41.3 in) Incl. Transport cart approx. 185 cm (72.8 in) Power supply: ~110/230 V, 10 A 	<ul style="list-style-type: none"> Weight approx. 565 kg (1245 lbs) Dimensions approx.: 205 x 185 x 110 cm (80.7 x 72.8 x 43.3 in) Power supply: ~110/230 V, 10 A
Transport cart (Optional)	<ul style="list-style-type: none"> Weight approx. 95 kg (209 lbs) Dimensions approx.: 65 x 115 x 45 cm (25.6 x 45.3 x 17.7 in) Capacity approx. 40 screen frames Manual frame feeding possible 	<ul style="list-style-type: none"> Customer specific production

