


Automotive filters

Automotive filters are designed to protect relevant mechanical and electronic components parts in the automotive sector. Sefar offers highly precise woven screens in monofilaments for applications such as security filters for valves, pumps and sensors. We can also supply depth filters where high dust holding capacity is needed.



Injection filters

Sefar AG

Hinterbissaustrasse 12 9410 Heiden Switzerland Phone +41 71 898 5700 Fax +41 71 898 5721

info@sefar.com

For fuel, CNG and AdBlue / SCR filters



Highly precise and secure filter

screens in a wide range of pore sizes

Excellent thermal and chemical

resistance

- Best possible flow rate
- Customer-specific colors
- Best processability
- SEFAR NITEX (PA), SEFAR

PEEKTEX (PEEK) screens

.....

Filters for hydraulic systems

For hydraulic brake filters, transmission filters, power steering filters and hydraulic cartridge systems:



Highly precise and secure filter

screens in a wide range of pore sizes

Excellent thermal and chemical

resistance


- Best possible flow rate
- SEFAR NITEX (PA), SEFAR PETEX

(PET) and SEFAR PEEKTEX

Sefar AG

Hinterbissaustrasse 12 9410 Heiden Switzerland Phone +41 71 898 5700 Fax +41 71 898 5721





Filters for the water system

We provide products for windshield wipers and water reservoirs:



Highly precise and secure filter
screens in a wide range of pore size
Excellent thermal and chemical

resistance

- Best possible flow rate
- SEFAR NITEX (PA), SEFAR

PROPYLTEX (PP) screens

- Customer-specific colors in PA
- Best processability

.....

Sefar AG

Hinterbissaustrasse 12 9410 Heiden Switzerland Phone +41 71 898 5700 Fax +41 71 898 5721

info@sefar.com



In-tank fuel pump filter and in-tank diesel filter



- High mechanical and chemical High capacity on defined particle size Best processability
 - SEFAR ACCUFLOW, SEFAR TETEX

MONO, SEFAR NITEX

AdBlue / SCR / DEF- Filters and sensor filters

Products to protect the AdBlue pump module, injection system and sensors in diesel exhaust conditioning.



High mechanical and chemical stability

High capacity on defined particle size

- Best processability
- SEFAR ACCUFLOW, SEFAR TETEX

MONO, SEFAR NITEX

Sefar AG

Hinterbissaustrasse 12 9410 Heiden Switzerland

Phone +41 71 898 5700 Fax +41 71 898 5721

info@sefar.com



Transmission, gear oil filtration

Suction and pressure filters manufactured using our open mesh fabrics combined with a wide range of depth media provide the ultimate filtration protection.



- Customer-specific solutions
- Combination of non-woven and woven fabric
- Open mesh for pleated elements
- Open mesh for last chance filtration

Diesel water separation

SEFAR ACCUFLOW is the top choice for coalescing, while an open mesh filter with a special hydrophobic treatment is best for water separation.



- SEFAR ACCUFLOW depth media for coalescing
- SEFAR PETEX (PET), SEFAR

NITEX (PA) hydrophobic range for

water separation

In-house media testing (based on

ISO 16332)

Sefar AG

Hinterbissaustrasse 12 9410 Heiden Switzerland Phone +41 71 898 5700 Fax +41 71 898 5721





IATF 16949 Automotive

Sefar's manufacturing system is geared towards providing lot-to-lot repeatability for critical parameters. This consistent quality allows automotive injection molders and filter element manufacturers to easily incorporate Sefar products into their manufacturing processes.

Your Benefits

Inherent material properties

- Good replacement for metal filters (thermal and chemical resistance)
- Easily molded (handling properties of synthetic fiber vs. wire)
- Consistent quality (IATF 16949)
- Useable in extreme temperature ranges and chemically aggressive environments

(PEEK fabrics)

Variety of conversion configurations

Sefar AG

Hinterbissaustrasse 12 9410 Heiden Switzerland Phone +41 71 898 5700 Fax +41 71 898 5721

info@sefar.com



Open mesh fabrics

- Exact and repeatable screening properties (high precision mesh opening)
- High flow rates (low pressure drop, maximized open area by use of fiber down to

24µm)

Adjustable hydrophobic levels, ranging from 100 to 135 degree contact angle

(surface modification)

Maximum technical range (materials, diameters and weaving patterns)

Closed mesh fabrics

- Highly efficient particle retention (closed mesh)
- Optimized flow rates
- Cleanliness (smooth surface)

Depth filter material

- Lower power consumption and minimal space requirement (low pressure drop)
- Protects pump systems (high particle retention capacity)
- Useable with all fuels and most liquids (elevated temperature fuel tests)
- Excellent bonding uniformity (latest ultrasonic bonding technology)
- Depth filter material for high capacity (60 µm material) applications
- Depth filter material for high efficiency (30 µm material) applications

Sefar AG

Hinterbissaustrasse 12 9410 Heiden Switzerland Phone +41 71 898 5700 Fax +41 71 898 5721

info@sefar.com



Proven test results for flat or converted materials (external approved test labs)

Available as roll goods or ribbons for injection molders

Locations



Sefar AG

Töberstrasse 4 9425 Thal – Switzerland Phone: +41 71 898 5700 Fax: +41 71 886 3504

E-Mail

Sefar AG

Hinterbissaustrasse 12 9410 Heiden Switzerland Phone: +41 71 898 5700 Fax: +41 71 898 5721

E-Mail

Sefar AG

Hinterbissaustrasse 12 9410 Heiden Switzerland Phone +41 71 898 5700 Fax +41 71 898 5721

info@sefar.com